

Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name : P3-ansep CIP

Product code : 116108E

Use of the : Cleaning product

Substance/Mixture

Substance type: : Mixture

For professional users only.

Product dilution information : 2.0 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Process cleaner. Cleaning In place (CIP) process

Recommended restrictions

on use

: Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.

PO Box 11; Winnington Avenue

Northwich, Cheshire, United Kingdom CW8 4DX

+ 44 (0)1606 74488 ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone : +441618841235

number +32-(0)3-575-5555 Trans-European

Date of Compilation/Revision : 14.08.2020 Version : 2.1

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Product AS SOLD

Corrosive to metals, Category 1	H290
Skin corrosion, Category 1	H314
Serious eye damage, Category 1	H318
Acute aquatic toxicity, Category 1	H400
Chronic aquatic toxicity, Category 2	H411

The classification of this product is based only on its extreme pH value (in accordance with current

116108E 1 / 17

European legislation).

Product AT USE DILUTION

Skin corrosion, Category 1 H314 Serious eye damage, Category 1 H318

The classification of this product is based only on its extreme pH value (in accordance with current European legislation).

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Product AS SOLD

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard

Statements

: EUH031

Contact with acids liberates toxic gas.

Precautionary Statements : Prevention:

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water

or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

sodium hydroxide sodium hypochlorite

Product AT USE DILUTION

Hazard pictograms



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.

Precautionary Statements : Prevention:

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off

116108E 2 / 17

immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

2.3 Other hazards

Product AS SOLD

Mixing this product with acid or ammonia releases chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Product AS SOLD Hazardous components

Chemical Name	CAS-No.	Classification	Concentration:
	EC-No.	REGULATION (EC) No 1272/2008	[%]
	REACH No.		
sodium hydroxide	1310-73-2	Skin corrosion Category 1A; H314	>= 5 - < 10
	215-185-5	Corrosive to metals Category 1; H290	
	01-2119457892-27		
sodium hypochlorite	7681-52-9	Nota B Skin corrosion Sub-category 1B;	>= 3 - < 5
	231-668-3	H314	
	01-2119488154-34	Serious eye damage Category 1; H318	
		Acute aquatic toxicity Category 1; H400	
		Chronic aquatic toxicity Category 1;	
		H410	
		Corrosive to metals Category 1; H290	

Product AT USE DILUTION Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
sodium hypochlorite	7681-52-9 231-668-3 01-2119488154-34	Skin corrosionSub-category 1B; H314 Serious eye damageCategory 1; H318 Acute aquatic toxicityCategory 1; H400 Chronic aquatic toxicityCategory 1; H410 Corrosive to metalsCategory 1; H290	< 0.1
Substances with a workp	lace exposure limit:		
sodium hydroxide	1310-73-2 215-185-5 01-2119457892-27	Skin corrosionCategory 1A; H314 Corrosive to metalsCategory 1; H290	>= 0.1 - < 0.25

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

Product AS SOLD

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

116108E 3 / 17

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.

Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention

immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give

anything by mouth to an unconscious person. If conscious, give 2

glasses of water. Get medical attention immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention

if symptoms occur.

Product AT USE DILUTION

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.

Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention

immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give

anything by mouth to an unconscious person. If conscious, give 2

glasses of water. Get medical attention immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention

if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Exposure to decomposition products may be a hazard to health.

Hazardous combustion

products

: Depending on combustion properties, decomposition products

may include following materials:

Carbon oxides

116108E 4 / 17

Oxides of phosphorus Hydrogen chloride metal oxides

5.3 Advice for firefighters

for firefighters

Special protective equipment : Use personal protective equipment.

Further information : Collect contaminated fire extinguishing water separately. This

> must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or

explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD

Advice for non-emergency personnel

: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable

materials.

Product AT USE DILUTION

Advice for non-emergency personnel

: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

: Do not allow contact with soil, surface or ground water. Environmental precautions

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with

non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material

116108E 5/17

or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up

: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.

For personal protection see section 8.

See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD

Advice on safe handling

: Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. Mixing this product with acid or ammonia releases chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Advice on safe handling

 Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling.
 Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities

Product AS SOLD

Requirements for storage areas and containers

: Do not store near acids. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Keep only in original packaging. Absorb spillage to prevent material damage.

Storage temperature : -5 °C to 30 °C

116108E 6 / 17

Packaging material : Suitable material: Plastic material

Unsuitable material: Aluminium, Mild steel

Product AT USE DILUTION

Requirements for storage areas and containers

: Do not store near acids. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses

Product AS SOLD

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Product AS SOLD

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
sodium hydroxide	1310-73-2	STEL	2 mg/m3	UKCOSSTD
sodium hydroxide	1310-73-2	STEL	2 mg/m3	UKCOSSTD
chlorine	7782-50-5	STEL	0.5 ppm	UKCOSSTD
			1.5 mg/m3	
chlorine	7782-50-5	STEL	0.5 ppm	UKCOSSTD
			1.5 mg/m3	

DNEL

sodium hydroxide	•	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3
		End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3

8.2 Exposure controls

Product AS SOLD

Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after

handling. Provide suitable facilities for quick drenching or flushing

of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles

Face-shield

116108E 7 / 17

Hand protection (EN 374) : Recommended preventive skin protection

Gloves Nitrile rubber butyl-rubber

Breakthrough time: 1 – 4 hours

Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4

mm or equivalent (please refer to the gloves

manufacturer/distributor for advise).

Gloves should be discarded and replaced if there is any indication

of degradation or chemical breakthrough.

Skin and body protection

(EN 14605)

: Personal protective equipment comprising: suitable protective

gloves, safety goggles and protective clothing including

appropriate safety shoes

Respiratory protection (EN

143, 14387)

: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified

respiratory protection equipment meeting EU

requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods

or procedures of work organization.

Product AT USE DILUTION Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing

of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN

166)

: Safety goggles Face-shield

Hand protection (EN 374) : Recommended preventive skin protection

Gloves Nitrile rubber butyl-rubber

Breakthrough time: 1 – 4 hours

Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4

mm or equivalent (please refer to the gloves

manufacturer/distributor for advise).

Gloves should be discarded and replaced if there is any indication

of degradation or chemical breakthrough.

Skin and body protection

(EN 14605)

: Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including

appropriate safety shoes

Respiratory protection (EN

143, 14387)

None required if airborne concentrations are maintained below the

exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU

requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by

116108E 8 / 17

technical means of collective protection or by measures, methods

or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Product AS SOLD Product AT USE DILUTION

Appearance : liquid liquid Colour : light yellow colourless Odour Chlorine : Chlorine : 13.5 - 14.0, 100 % 12.7 pΗ

Flash point : Not applicable.

Odour Threshold : Not applicable and/or not determined for the mixture Melting point/freezing point : Not applicable and/or not determined for the mixture

Initial boiling point and

boiling range

: > 100 °C

Evaporation rate : Not applicable and/or not determined for the mixture Flammability (solid, gas) : Not applicable and/or not determined for the mixture Upper explosion limit : Not applicable and/or not determined for the mixture Lower explosion limit Not applicable and/or not determined for the mixture Vapour pressure : Not applicable and/or not determined for the mixture Not applicable and/or not determined for the mixture Relative vapour density

: 1.16 - 1.2 Relative density Water solubility : soluble

Solubility in other solvents : Not applicable and/or not determined for the mixture Partition coefficient: n-: Not applicable and/or not determined for the mixture

octanol/water Auto-ignition temperature

Thermal decomposition

Viscosity, kinematic

: Not applicable and/or not determined for the mixture : Not applicable and/or not determined for the mixture : Not applicable and/or not determined for the mixture

: Not applicable and/or not determined for the mixture Explosive properties

Oxidizing properties : Yes

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD

116108E 9/17

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Mixing this product with acid or ammonia releases chlorine gas.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Acids Metals

Mild steel Aluminium

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials: Carbon oxides Oxides of phosphorus Hydrogen chloride metal oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product AS SOLD

exposure

Information on likely routes of : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : There is no data available for this product.

Acute inhalation toxicity : There is no data available for this product.

Acute dermal toxicity : There is no data available for this product.

Skin corrosion/irritation : There is no data available for this product.

Serious eye damage/eye

irritation

: There is no data available for this product.

Respiratory or skin

sensitization

: There is no data available for this product.

Carcinogenicity : There is no data available for this product.

116108E 10 / 17

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : sodium hypochlorite

LD50 rat: 5,230 mg/kg

Components

Acute dermal toxicity : sodium hypochlorite

LD50 rabbit: > 10,000 mg/kg

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact : Redness, Pain, Corrosion

116108E 11 / 17

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Section: 12. ECOLOGICAL INFORMATION

Product AS SOLD 12.1 Ecotoxicity

Environmental Effects : Very toxic to aquatic life. Toxic to aquatic life with long lasting

effects.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other : no data available

aquatic invertebrates

Toxicity to algae : no data available

Components

Toxicity to fish : sodium hypochlorite

96 h EC50: 0.14 mg/l

Components

Toxicity to daphnia and other : sodium hydroxide

aquatic invertebrates

sodium hydroxide 48 h EC50: 40 mg/l

sodium hypochlorite 48 h EC50: 0.071 mg/l

12.2 Persistence and degradability

Product

no data available

Components

Biodegradability : sodium hydroxide

Result: Not applicable - inorganic

sodium hypochlorite

Result: Not applicable - inorganic

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

116108E 12 / 17

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be

either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or

higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD

Product : The product should not be allowed to enter drains, water courses

or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an

approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken

to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local,

state, and federal regulations.

Guidance for Waste Code

selection

: Inorganic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the

toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC)

and local regulations.

Product AT USE DILUTION

Product

: Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal

facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken

to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local,

state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

116108E 13 / 17

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : 3266

14.2 UN proper shipping : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.

name

(sodium hydroxide, sodium hypochlorite)

14.3 Transport hazard : 8

class(es)

14.4 Packing group : II14.5 Environmental hazards : Yes

14.6 Special precautions for : None

user

Air transport (IATA)

14.1 UN number : 3266

14.2 UN proper shipping : Corrosive liquid, basic, inorganic, n.o.s.

name

(sodium hydroxide, sodium hypochlorite)

14.3 Transport hazard : 8

class(es)

14.4 Packing group : II 14.5 Environmental hazards : Yes

14.6 Special precautions for

user

: None

Sea transport (IMDG/IMO)

14.1 UN number : 3266

14.2 UN proper shipping : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.

name

(sodium hydroxide, sodium hypochlorite)

14.3 Transport hazard : 8

class(es)

14.4 Packing group : II 14.5 Environmental hazards : Yes

14.6 Special precautions for

user

: None

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC

Code

: Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents Regulation EC 648/2004 : less than 5 %: Phosphonates, Chlorine-based bleaching agents

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)

Regulations.

116108E 14 / 17

The Control of Substances Hazardous to Health Regulations. Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Corrosive to metals 1, H290	Calculation method
Skin corrosion 1, H314	Based on product data or assessment
Serious eye damage 1, H318	Based on product data or assessment
Acute aquatic toxicity 1, H400	Calculation method
Chronic aquatic toxicity 2, H411	Calculation method

Full text of H-Statements

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM -American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL -Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number -European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS - Globally Harmonized System: GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

116108E 15 / 17

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Process cleaner. Cleaning In place (CIP) process

Life Cycle Stage : Use at industrial sites

Product category : PC35 Washing and cleaning products (including solvent based

products)

Contributing scenario controlling environmental exposure for:

Environmental release : ERC4 Industrial use of processing aids in processes and

category products, not becoming part of articles

Daily amount per site : 50 kg

Type of Sewage Treatment : Municipal sewage treatment plant

Plant

Contributing scenario controlling worker exposure for:

Process category : **PROC8b** Transfer of substance or preparation (charging/

discharging) from/ to vessels/ large containers at

dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures

: Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

116108E 16 / 17

: Indoor

P3-ansep CIP

Contributing scenario controlling worker exposure for:

Process category : **PROC1** Use in closed process, no likelihood of exposure

Exposure duration : 480 min

Operational conditions and

risk management measures

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

116108E 17 / 17