

OxyDes Rapid

Description: OxyDes Rapid is a ready to use spray disinfectant

designed for use in production areas in the food and

beverage industry where water is undesirable

Product strengths:

Excellent disinfecting properties

• QAC, ethanol free formulation

Kosher and Halal compliant

• No rinse requirement after application

Properties

Concentrate Appearance: clear, colourless liquid *

Storage stability: 0 to 35 °C

Solubility: at 20 °C miscible with water in any

tuproportion

Density: 0.975 - 0.995 g/cm³ *

P content: 0.06 %

N content: 0.00 %

S content 0.00 %

COD: not applicable

Flash point: 35.5 °C

pH: 2.01 – 2.30 *

Foam characteristics: non-foaming

^{*} Parameters subject to incoming goods control

Material compatibility

Metal

OxyDes Rapid is, under the application conditions, compatible with materials available in the F&B industry described as follows.

The material compatibility for standard metals has been tested according to standard DIN 50905 at 20°C and for 96 h. The weight difference has been calculated as g per m² per hour.

Material	g/m²h
Stainless steel (DIN 1.4301 = AISI 304)	0,000
Aluminium 99,5%*	0,048
AIMg3*	0,051
Copper*	0,202
*colour changes might occur	

OxyDes Rapid is fully compatible with stainless steel.

When using **OxyDes Rapid** on aluminium and its alloy color change has been observed.

OxyDes Rapid is **not** recommended on his use on copper and its alloys, such as brass, neither on mild steel nor carbon steel.

Please try on an uncritical surface before use.

Other materials

The compatibility for standard plastics and sealing materials has been tested according to standard DIN ISO 1817 and DIN EN ISO 175.

OxyDes Rapid is compatible with the common plastic and sealing materials such as PVDF, PVC, HDPE, PP, POM, EPDM, FKM, HFFKM, NBR.

OxyDes Rapid is not recommended for PC and PMMA.

For sensitive materials, after the recommended contact time, any excess amount of liquid should be removed with a dry clean wipe or towel.

In view of the wide range of different materials in use, it is advisable to test suitability as necessary.

Microbiology

EN 1276 Bactericidal Efficacy – Suspension					
	Test organisms	Temperature	Clean conditions (0.3 g/L BSA)	Dirty conditions (3.0 g/L BSA)	
Pass criteria	Bacteria - Staphylococcus aureus	20°C	1 min	5 min	
>5 log - Pseudomonas aeruginosa reduction - Escherichia coli - Enterococcus hirae	10°C	1 min	5 min		

EN 1650 Yeasticidal efficacy – Suspension					
	Test organisms	Temperature	Clean conditions (0.3 g/L BSA)	Dirty conditions (3.0 g/L BSA)	
Pass criteria	Yeast - Candida albicans	20°C	1 min	5 min	
>4 log reduction		10°C	1 min	5 min	

EN 13697 Bactericidal, Yeasticidal efficacy – Surface					
	Test organisms	Temperature	Clean conditions (0.3 g/L BSA)	Dirty conditions (3.0 g/L BSA)	
Pass criteria Bactericidal	Bacteria - Staphylococcus aureus - Enterococcus hirae	20°C	1 min	5 min	
efficacy >4 log reduction	Escherichia coliPseudomonas aeruginosaSalmonella typhimurium	10°C	1 min	5 min	
Yeasticidal	Yeast - Candida albicans	20°C	1 min	5 min	
efficacy >3 log reduction		10°C	1 min	5 min	

Conclusion:

OxyDes Rapid demonstrates a bactericidal and yeasticidal effect as surface disinfectant, when applied undiluted by spraying with or without wiping at temperatures of 10 - 20°C at a contact time of 5 min for dirty surfaces, respectively 30 sec for cleaned surfaces for the food and feed area.

Disinfection

• Spray undiluted on the surface

• Spraying distance to surface: 0.30 m

• Recommended dosage: 10 - 30 ml/m²

• Contact time 1 - 5 minutes

- Allow surfaces to air dry or remove remaining liquid with a clean wipe
- Rinsing with water is not necessary

Important indications!

- Effluent, containing chemicals, must only be discharged according to the local regulations
- Chemicals containing effluent must only be discharged into the biological treatment station after passing the neutralization- and buffer tank
- When discharging chemically polluted effluent, it is essential to pay specific attention to the bacteria toxicity of this water. This is especially important when dealing with biocide containing effluents and anaerobic sewage plants
- In case of doubt please seek advice from our technical service

Safety

The relevant hazards identifications of **OxyDes Rapid** are given in the EC Safety Data Sheet. If any questions arise in this context, please contact your Ecolab representative.

OxyDes Rapid is not intended to be applied in excessive amounts in small closed rooms. In case of contact with eyes, rinse immediately with water for 20 minutes and seek medical advice. Do not spray on flames or burning entities. During spraying, the room must be sufficiently aerated.

Although not mandatory, it is recommended to use protective equipment to avoid excessive exposure to skin.

Use product safely. Always read the label and product information before use.

Ecolab Deutschland GmbH hereby confirms that the BPR Union Authorisation has now been formally published in COMMISSION IMPLEMENTING REGULATION (EU) 2022/1423 of 22 July 2022 granting a Union Authorisation for the biocidal product family 'Hydrogen Peroxide Family 1'. The authorisation is published in the link: https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32022R1423&qid=1658326396245 COMMISSION IMPLEMENTING REGULATION (EU) 2022/1423 is a Union Authorisation, meaning that **OxyDes Rapid** can be marketed in the 27 European Union Member States and is valid from 15 September 2022 until 31 August 2032.

The Biocidal Products Regulation (BPR, Regulation (EU) 528/2012) that concerns the placing on the market and use of biocidal products in the European Union (EU) is in force and offers a harmonized and more centralized authorisation and approval process for biocidal products at a European level and aims to harmonize the market.

Following the publication of COMMISSION IMPLEMENTING REGULATION (EU) 2022/1423, the existing (pre-BPR) local approvals will be phased out.

The statements, information and data presented herein are believed to be accurate and reliable. The information describes the characteristic features of **OxyDes Rapid** in ordinary use but cannot be taken as a guarantee, express warranty or implied warranty for the suitability for a particular purpose and shall not extend mandatory warranty rights (if any). The specifications and performance may vary subject to the operational conditions. Since numerous parameters will influence product performance and applicability, this information does not exonerate the user from liability with respect to the suitability of the product and the appropriate safety measures to be taken. Moreover, a possible infringement of patent rights must be avoided at all times.

(Version July 2023)

