

# Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

Product name : P3-oxonia active

Product code : 106965E

Use of the : Biocide

Substance/Mixture

Substance type: : Mixture

For professional users only.

Product dilution information : 3.0 %

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Surface disinfectant. Spray and rinse manual process

Process cleaner. Cleaning In place (CIP) process Disinfection product. Semi-automatic process

Recommended restrictions

on use

: Reserved for industrial and professional use.

## 1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.

PO Box 11; Winnington Avenue

Northwich, Cheshire, United Kingdom CW8 4DX

+ 44 (0)1606 74488 ccs@ecolab.com

### 1.4 Emergency telephone number

Emergency telephone : +441618841235

number +32-(0)3-575-5555 Trans-European

Date of Compilation/Revision : 31.05.2021 Version : 2.3

## **Section: 2. HAZARDS IDENTIFICATION**

### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

## **Product AS SOLD**

Oxidizing liquids, Category 2	H272
Corrosive to metals, Category 1	H290
Acute toxicity, Category 4	H302
Acute toxicity, Category 4	H332
Skin corrosion, Category 1	H314

106965E 1 / 22

Serious eye damage, Category 1 H318 Specific target organ toxicity - single exposure, Category 3, H335

Respiratory system

Chronic aquatic toxicity, Category 1 H410

**Product AT USE DILUTION** 

Chronic aquatic toxicity, Category 3 H412

### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

**Product AS SOLD** 

Hazard pictograms









Signal Word : Danger

**Hazard Statements** : H272 May intensify fire; oxidiser.

> May be corrosive to metals. H290

Harmful if swallowed or if inhaled. H302 + H332

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting

effects.

: Prevention: **Precautionary Statements** 

> P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

Avoid release to the environment. P273

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water

or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

> for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Hydrogen peroxide

Acetic acid Peracetic acid

**Product AT USE DILUTION** 

Hazard Statements : H412 Harmful to aquatic life with long lasting effects.

**Precautionary Statements** : Prevention:

> P273 Avoid release to the environment.

## 2.3 Other hazards

## **Product AS SOLD**

106965E 2/22

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

# Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

# Product AS SOLD Hazardous components

Chemical Name	CAS-No.	Classification	Concentration
	EC-No. REACH No.	REGULATION (EC) No 1272/2008	: [%]
Hydrogen peroxide	7722-84-1 231-765-0 01-2119485845-22	Nota B Oxidizing liquids Category 1; H271 Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Skin corrosion Category 1A; H314 Serious eye damage/eye irritation	>= 25 - < 30
		Category 1 8 - 100 % Serious eye damage/eye irritation Category 2A 5 - 8 %	
		Oxidizing liquids Category 1 70 - 100 % Oxidizing liquids Category 2 50 - 70 %	
		Skin corrosion/irritation Category 1A 70 - 100 % Skin corrosion/irritation Category 1B 50 - 70 %	
		Skin corrosion/irritation Category 2 35 - 50 % Specific target organ toxicity - single exposure Category 3 H335 35 - 100 %	
Acetic acid	64-19-7 200-580-7 01-2119475328-30	Nota B Flammable liquids Category 3; H226 Skin corrosion Sub-category 1A; H314 Serious eye damage Category 1; H318	>= 5 - < 10
		Skin corrosion Category 1A H314 >= 90 % Skin corrosion Category 1B	
		H314 25 - < 90 % Skin irritation Category 2 H315 10 - < 25 % Eye irritation Category 2 H319 10 - < 25 %	
Peracetic acid	79-21-0 201-186-8 01-2119531330-56	Flammable liquids Category 3; H226 Organic peroxides Type D; H242 Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Category 1A; H314 Acute aquatic toxicity Category 1; H400 Specific target organ toxicity - single exposure Category 3; H335 Chronic aquatic toxicity Category 1; H410	>= 2.5 - < 5
		Specific target organ toxicity - single exposure Category 3	

106965E 3 / 22

	H335 >= 1 %	
	M = 1	
	M(Chronic) = 10	

# Product AT USE DILUTION Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Peracetic acid	79-21-0 201-186-8 01-2119531330-56	Flammable liquidsCategory 3; H226 Organic peroxidesType D; H242 Acute toxicityCategory 4; H302 Acute toxicityCategory 4; H332 Acute toxicityCategory 4; H312 Skin corrosionCategory 1A; H314 Acute aquatic toxicityCategory 1; H400 Specific target organ toxicity - single exposureCategory 3; H335 Chronic aquatic toxicityCategory 1; H410  Specific target organ toxicity - single exposure Category 3 H335 >= 1 % M = 1 M(Chronic) = 10	>= 0.1 - < 0.25
Substances with a workp			
Hydrogen peroxide	7722-84-1 231-765-0 01-2119485845-22	Oxidizing liquidsCategory 1; H271 Acute toxicityCategory 4; H302 Acute toxicityCategory 4; H332 Skin corrosionCategory 1A; H314  Serious eye damage/eye irritation Category 1 8 - 100 % Serious eye damage/eye irritation Category 2A 5 - 8 % Oxidizing liquids Category 1 70 - 100 % Oxidizing liquids Category 2 50 - 70 % Skin corrosion/irritation Category 1A 70 - 100 % Skin corrosion/irritation Category 1B 50 - 70 % Skin corrosion/irritation Category 2 35 - 50 % Specific target organ toxicity - single exposure Category 3 H335 35 - 100 %	>= 0.5 - < 1
Acetic acid	64-19-7 200-580-7 01-2119475328-30	Flammable liquidsCategory 3; H226 Skin corrosionSub-category 1A; H314 Serious eye damageCategory 1; H318  Skin corrosion Category 1A H314 >= 90 % Skin corrosion Category 1B H314 25 - < 90 % Skin irritation Category 2 H315 10 - < 25 % Eye irritation Category 2 H319 10 - < 25 %	>= 0.1 - < 0.25

106965E 4 / 22

For the full text of the H-Statements mentioned in this Section, see Section 16.

## Section: 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

**Product AS SOLD** 

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.

Wash clothing before reuse. Thoroughly clean shoes before

reuse. Get medical attention immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give

anything by mouth to an unconscious person. Get medical

attention immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention.

**Product AT USE DILUTION** 

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### 4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## **Section: 5. FIREFIGHTING MEASURES**

### **Product AS SOLD**

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Special protective equipment for firefighters

Oxidizer. Contact with other material may cause fire.

Oxidizer; material is an oxidizer which may readily react with other

materials, especially upon heating.

Hazardous combustion

products

: Depending on combustion properties, decomposition products

may include following materials:

106965E 5 / 22

Carbon oxides

### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In case of fire, wear a full face positive-pressure self contained

breathing apparatus and protective suit.

Further information : Use water spray to cool unopened containers. Collect

> contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe

### Section: 6. ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

### **Product AS SOLD**

Advice for non-emergency personnel

: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency

responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable

materials.

### **Product AT USE DILUTION**

Advice for non-emergency

personnel

: Ensure clean-up is conducted by trained personnel only. Refer to

protective measures listed in sections 7 and 8.

Advice for emergency

responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable

materials.

### 6.2 Environmental precautions

### **Product AS SOLD**

Environmental precautions

: Do not allow contact with soil, surface or ground water.

## **Product AT USE DILUTION**

**Environmental precautions** 

: Do not allow contact with soil, surface or ground water.

### 6.3 Methods and materials for containment and cleaning up

### **Product AS SOLD**

Methods for cleaning up

Stop leak if safe to do so. Isolate the waste do not allow it to come into contact with incompatible materials. For small spills contain with sand or vermiculite and dilute the contained product at least 10 times with water. Transfer to an open topped container and remove to a safe place for neutralization\* / disposal. For large spills contain spill and evacuate the area, leave until the reaction subsides, then collect up for disposal. Obtain consent from the local water company / authority if considering discharge to sewer. \*NEUTRALIZATION : once diluted, neutralize with a suitable alkali such as sodium bicarbonate. Combustible materials exposed to

106965E 6/22

this product should be rinsed immediately with large amounts of water to ensure that all product is removed. Residual product which is allowed to dry on organic materials such as rags, cloths, paper, fabrics, cotton, leather, wood, or other combustibles may spontaneously ignite and result in a fire.

### **Product AT USE DILUTION**

Methods for cleaning up

: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information. For personal protection see section 8. See Section 13 for additional waste treatment information.

### **Section: 7. HANDLING AND STORAGE**

### 7.1 Precautions for safe handling

### **Product AS SOLD**

Advice on safe handling

: Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

## **Product AT USE DILUTION**

Advice on safe handling

: Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after

handling.

### 7.2 Conditions for safe storage, including any incompatibilities

### **Product AS SOLD**

Requirements for storage areas and containers

: Keep in a cool, well-ventilated place. Keep away from reducing agents. Keep away from strong bases. Keep away from combustible material. Absorb spillage to prevent material damage. Keep out of reach of children. Keep container tightly closed. Keep only in original packaging. Store in suitable labeled containers. Pressure bursts may occur due to gas evolution if the container is

106965E 7 / 22

not adequately vented.

Storage temperature : 0 °C to 30 °C

Packaging material : Suitable material: Plastic material

Unsuitable material: Mild steel, Aluminium

**Product AT USE DILUTION** 

Requirements for storage areas and containers

: Keep out of reach of children. Keep container tightly closed. Store

in suitable labeled containers.

### 7.3 Specific end uses

**Product AS SOLD** 

Specific use(s) : Surface disinfectant. Spray and rinse manual process

Process cleaner. Cleaning In place (CIP) process Disinfection product. Semi-automatic process

## Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters

### **Product AS SOLD**

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrogen peroxide	7722-84-1	TWA	1 ppm 1.4 mg/m3	UKCOSSTD
		STEL	2 ppm 2.8 mg/m3	UKCOSSTD
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m3	2017/164/EU
Further information	Indica	ntive	-	
		STEL	20 ppm 50 mg/m3	2017/164/EU
Further information	Indica	ntive	-	
		STEL	20 ppm 50 mg/m3	UKCOSSTD
		TWA	10 ppm 25 mg/m3	UKCOSSTD

## DNEL

Hydrogen peroxide	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 3 mg/m3
		End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1.4 mg/m3
Peracetic acid	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 0.6 mg/m3

106965E 8 / 22

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Acute systemic effects

Value: 0.6 mg/m3

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 0.6 mg/m3

End Use: Workers

**Exposure routes: Inhalation** 

Potential health effects: Acute local effects

Value: 0.6 mg/m3

End Use: Workers

Exposure routes: Skin contact

Potential health effects: Acute local effects

Value: 0.12

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 0.6 mg/m3

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Acute systemic effects

Value: 0.6 mg/m3

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 0.6 mg/m3

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Acute local effects

Value: 0.3 mg/m3

# PNEC

Peracetic acid	:	Fresh water Value: 0.000224 mg/l
		Fresh water sediment Value: 0.00018 mg/kg
		Water Value: 0.051 mg/l
		Soil Value: 0.32 mg/kg

### 8.2 Exposure controls

106965E 9 / 22

# Product AS SOLD Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after

handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles

Face-shield

Hand protection (EN 374) : Recommended preventive skin protection

Gloves Nitrile rubber butyl-rubber

Breakthrough time: 1 – 4 hours

Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4

mm or equivalent (please refer to the gloves

manufacturer/distributor for advise).

Gloves should be discarded and replaced if there is any indication

of degradation or chemical breakthrough.

Skin and body protection

(EN 14605)

: Personal protective equipment comprising: suitable protective

gloves, safety goggles and protective clothing including

appropriate safety shoes

Respiratory protection (EN

143, 14387)

: None required if airborne concentrations are maintained below the

exposure limit listed in Exposure Limit Information. Use certified

respiratory protection equipment meeting EU

requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods

or procedures of work organization.

# Product AT USE DILUTION Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

Eye/face protection (EN

166)

: No special protective equipment required.

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection

(EN 14605)

: No special protective equipment required.

106965E 10 / 22

Respiratory protection (EN

143, 14387)

: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

### **Environmental exposure controls**

General advice : Consider the provision of containment around storage vessels.

## Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

Product AS SOLD Product AT USE DILUTION

Appearance : liquid liquid
Colour : colourless colourless
Odour : pungent characteristic

pH : 0.5 - 1.5, 100 % 2.5

Flash point : 100 °C closed cup, Does not sustain combustion.

Odour Threshold : Not applicable and/or not determined for the mixture

Melting point/freezing point : Not applicable and/or not determined for the mixture

Initial boiling point and

boiling range

: Not applicable and/or not determined for the mixture

Evaporation rate : Not applicable and/or not determined for the mixture Flammability (solid, gas) : Not applicable and/or not determined for the mixture Upper explosion limit : Not applicable and/or not determined for the mixture Lower explosion limit : Not applicable and/or not determined for the mixture Vapour pressure : Not applicable and/or not determined for the mixture Relative vapour density : Not applicable and/or not determined for the mixture

Relative density : 1.11 - 1.13
Water solubility : soluble

Solubility in other solvents : Not applicable and/or not determined for the mixture Partition coefficient: n- : Not applicable and/or not determined for the mixture

octanol/water

Auto-ignition temperature : Not applicable and/or not determined for the mixture

Thermal decomposition : Not applicable and/or not determined for the mixture

Viscosity, kinematic : Not applicable and/or not determined for the mixture

Explosive properties : Not applicable and/or not determined for the mixture

Oxidizing properties : YesThe substance or mixture is classified as oxidizing with the category 2.

#### 9.2 Other information

106965E 11 / 22

VOC : Not applicable.

## Section: 10. STABILITY AND REACTIVITY

### **Product AS SOLD**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Contamination may result in dangerous pressure increases - closed containers may rupture.

## 10.3 Possibility of hazardous reactions

Do not mix with bleach or other chlorinated products - will cause chlorine gas.

#### 10.4 Conditions to avoid

Direct sources of heat. Exposure to sunlight.

### 10.5 Incompatible materials

Organic materials

Metals

**Bases** 

Mild steel

Aluminium

### 10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials: Carbon oxides

## Section: 11. TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects

**Product AS SOLD** 

Information on likely routes of : Inhalation, Eye contact, Skin contact

exposure

**Product** 

Acute oral toxicity : Acute toxicity estimate : 1,550 mg/kg

: 4 h Acute toxicity estimate : > 20 mg/l Acute inhalation toxicity

Test atmosphere: vapour

: Acute toxicity estimate : > 2,000 mg/kg Acute dermal toxicity

Skin corrosion/irritation : There is no data available for this product.

106965E 12 / 22

Serious eye damage/eye

irritation

: There is no data available for this product.

Respiratory or skin

sensitization

: There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : Hydrogen peroxide LD50 rat: 486 mg/kg

Acetic acid LD50 rat: 3,310 mg/kg

Components

Acute inhalation toxicity : Hydrogen peroxide 4 h LC50 rat: 11 mg/l

Test atmosphere: vapour

Peracetic acid 4 h LC50 rat: 1.5 mg/l

Test atmosphere: dust/mist

Components

Acute dermal toxicity : Acetic acid LD50 rabbit: 1,060 mg/kg

**Potential Health Effects** 

**Product AS SOLD** 

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause respiratory tract irritation. May cause nose, throat, and

lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

**Product AT USE DILUTION** 

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

106965E 13 / 22

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

## **Experience with human exposure**

**Product AS SOLD** 

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

**Product AT USE DILUTION** 

Eye contact : No symptoms known or expected.

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

### Section: 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

**Product AS SOLD** 

Environmental Effects : Very toxic to aquatic life with long lasting effects.

**Product AT USE DILUTION** 

Environmental Effects : Harmful to aquatic life with long lasting effects.

**Product AS SOLD** 

**Product** 

Toxicity to fish : no data available

Toxicity to daphnia and other : no data available

aquatic invertebrates

Toxicity to algae : no data available

Components

Toxicity to fish : Acetic acid96 h LC50 Oncorhynchus mykiss (rainbow trout): >

1,000 mg/l

Peracetic acid96 h LC50: 0.8 mg/l

Components

Toxicity to daphnia and other

aquatic invertebrates

: Acetic acid48 h EC50 Daphnia magna (Water flea): 39.6 mg/l

Peracetic acid48 h EC50: 0.73 mg/l

Components

Toxicity to algae : Hydrogen peroxide72 h EC50: 1.38 mg/l

Acetic acid72 h EC50 Skeletonema costatum (marine diatom): >

106965E 14 / 22

1,000 mg/l

Peracetic acid72 h EC50: 0.7 mg/l

## 12.2 Persistence and degradability

### **Product**

no data available

### Components

Biodegradability : Hydrogen peroxideResult: Not applicable - inorganic

Acetic acidResult: Readily biodegradable.

Peracetic acidResult: Readily biodegradable.

### 12.3 Bioaccumulative potential

no data available

### 12.4 Mobility in soil

no data available

### 12.5 Results of PBT and vPvB assessment

## **Product**

Assessment : This substance/mixture contains no components considered to be

either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or

higher.

## 12.6 Other adverse effects

no data available

### Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

### 13.1 Waste treatment methods

**Product AS SOLD** 

Product : The product should not be allowed to enter drains, water courses

or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an

approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken

to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local,

state, and federal regulations.

Guidance for Waste Code : Inorganic wastes containing dangerous substances. If this product

106965E 15 / 22

selection is used in any further processes, the final user must redefine and

assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC)

and local regulations.

**Product AT USE DILUTION** 

Product : The product should not be allowed to enter drains, water courses

or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an

approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken

to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local,

state, and federal regulations.

## **Section: 14. TRANSPORT INFORMATION**

#### **Product AS SOLD**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : 3149

14.2 UN proper shipping : HYDROGEN PEROXIDE AND PEROXYACETIC ACID

name MIXTURE, STABILIZED

14.3 Transport hazard : 5.1 (8)

class(es)

14.4 Packing group : II 14.5 Environmental hazards : Yes

14.6 Special precautions for

user

: None

Air transport (IATA)

14.1 UN number : 3149

14.2 UN proper shipping : Hydrogen peroxide and peroxyacetic acid mixture stabilized

name

user

14.3 Transport hazard : 5.1 (8)

class(es)

14.4 Packing group : II 14.5 Environmental hazards : Yes

14.6 Special precautions for

•

: None

Sea transport (IMDG/IMO)

14.1 UN number : 3149

14.2 UN proper shipping : HYDROGEN PEROXIDE AND PEROXYACETIC ACID

name MIXTURE, STABILIZED

14.3 Transport hazard : 5.1 (8)

class(es)

106965E 16 / 22

14.4 Packing group : II14.5 Environmental hazards : Yes

14.6 Special precautions for

user

: None

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC

Code

: Not applicable.

# Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture **Regulation (EU) 2019/1148 on the marketing and use of explosives precursors**This product is regulated (containing reportable or/and restricted substances) by Regulation (EU) 2019/1148 (explosives precursors): all suspicious transactions, significant disappearances and thefts should be reported to the relevant national contact point.

Seveso III: Directive : OXIDIZING LIQUIDS AND SOLIDS P8

2012/18/EU of the European Parliament and of the Council on the control of major-

Lower tier: 50 t Upper tier: 200 t

accident hazards involving ENVIRONMENTAL HAZARDS E1

dangerous substances. Lower tier: 100 t
Upper tier: 200 t

### **National Regulations**

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)

Regulations.

The Control of Substances Hazardous to Health Regulations.

Health and Safety at Work Act.

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

### **Section: 16. OTHER INFORMATION**

## Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Oxidizing liquids 2, H272	Based on product data or assessment
Corrosive to metals 1, H290	Based on product data or assessment
Acute toxicity 4, H302	Calculation method
Acute toxicity 4, H332	Calculation method
Skin corrosion 1, H314	Based on product data or assessment
Serious eye damage 1, H318	Based on product data or assessment
Specific target organ toxicity - single exposure	Calculation method
3, H335	
Chronic aquatic toxicity 1, H410	Calculation method

### **Full text of H-Statements**

H226 Flammable liquid and vapour. H242 Heating may cause a fire.

106965E 17 / 22

H271	May cause fire or explosion; strong oxidiser.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM -American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL -Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number -European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan): ErCx – Concentration associated with x% growth rate response: GHS - Globally Harmonized System: GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB -Very Persistent and Very Bioaccumulative

### **Further information**

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

106965E 18 / 22

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Annex: Exposure Scenarios** 

Exposure Scenario: Process cleaner. Cleaning In place (CIP) process

Life Cycle Stage : Use at industrial sites

Product category : PC35 Washing and cleaning products (including solvent based

products)

Contributing scenario controlling environmental exposure for:

Environmental release

category

: ERC4

Industrial use of processing aids in processes and

products, not becoming part of articles

Daily amount per site : 50 kg

Type of Sewage Treatment

Plant

: Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC8b** Transfer of substance or preparation (charging/

discharging) from/ to vessels/ large containers at

dedicated facilities

Exposure duration : 60 min

Operational conditions and

risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC1** Use in closed process, no likelihood of exposure

Exposure duration : 480 min

Operational conditions and risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

106965E 19 / 22

Skin Protection : see section 8

Respiratory Protection : see section 8

Exposure Scenario: Disinfection product. Semi-automatic process

Life Cycle Stage : Use at industrial sites

Product category : PC35 Washing and cleaning products (including solvent based

products)

Contributing scenario controlling environmental exposure for:

Environmental release : ERC4 Industrial use of processing aids in processes and

category products, not becoming part of articles

Daily amount per site : 50 kg

Type of Sewage Treatment : Municipal sewage treatment plant

Plant

Contributing scenario controlling worker exposure for:

Process category : PROC8b Transfer of substance or preparation (charging/

discharging) from/ to vessels/ large containers at

dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC4** Use in batch and other process (synthesis) where

opportunity for exposure arises

Exposure duration : 480 min

Operational conditions and risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

106965E 20 / 22

Exposure Scenario: Surface disinfectant. Spray and rinse manual process

Life Cycle Stage : Widespread use by professional workers

Product category : PC35 Washing and cleaning products (including solvent based

products)

Contributing scenario controlling environmental exposure for:

Environmental release

category

ERC8a

Wide dispersive indoor use of processing aids in open

systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment

Plant

Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and

risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/

discharging) from/ to vessels/ large containers at non-

dedicated facilities

Exposure duration : 60 min

Operational conditions and

risk management measures

: Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC11** Non industrial spraying

Exposure duration : 60 min

106965E 21 / 22

# SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

# P3-oxonia active

Operational conditions and

risk management measures

: Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

106965E 22 / 22