

**TOPAZ LD1****Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : TOPAZ LD1

Product code : 116656E

Use of the Substance/Mixture : Cleaning product

Substance type: : Mixture

**For professional users only.**

Product dilution information : 5.0 %

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : General purpose cleaner. Manual process  
Foam cleaner. Semi-Automatic with venting process  
Foam cleaner. Semi-Automatic without venting process

Recommended restrictions on use : Reserved for industrial and professional use.

**1.3 Details of the supplier of the safety data sheet**

Company : Ecolab Ltd.  
PO Box 11; Winnington Avenue  
Northwich, Cheshire, United Kingdom CW8 4DX  
+ 44 (0)1606 74488  
ccs@ecolab.com

**1.4 Emergency telephone number**

Emergency telephone number : +441618841235  
+32-(0)3-575-5555 Trans-European

Poison Information Centre telephone number : For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 28.06.2023

Version : 2.6

**Section: 2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)****Product AS SOLD**

Eye irritation, Category 2

H319

**TOPAZ LD1****Product AT USE DILUTION**

Not a hazardous substance or mixture.

**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)****Product AS SOLD**

Hazard pictograms

:



Signal Word

: Warning

Hazard Statements

: H319

Causes serious eye irritation.

Precautionary Statements

: **Prevention:**  
P280e

Wear eye protection/face protection.

**Product AT USE DILUTION**

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

**2.3 Other hazards****Product AS SOLD**

None known.

**Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS****3.2 Mixtures****Product AS SOLD****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 01-2119475104-44	Eye irritation Category 2; H319	>= 2.5 - < 5
Sodium p-cumenesulphonate	15763-76-5 239-854-6 01-2119489411-37	Eye irritation Category 2; H319	>= 2.5 - < 5
Fattyalcohol ethoxylates =/ $\leq$ C15 and =/ $\leq$ 5EO	68213-23-0 01-2119489387-20	Acute toxicity Category 4; H302 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 1 - < 2.5
Alkylamineoxides	3332-27-2 222-059-3 01-2119949262-37	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 2; H411	>= 0.5 - < 1
Amines, C12-14	308062-28-4	Acute toxicity Category 4; H302	>= 0.5 - < 1

**TOPAZ LD1**

alkyldimethyl, N-oxides	01-2119490061-47	Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 2; H411	
		M = 1	

**Product AT USE DILUTION**  
**Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Substances with a workplace exposure limit :			
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 01-2119475104-44	Eye irritation Category 2; H319	>= 0.1 - < 0.25

For the full text of the H-Statements mentioned in this Section, see Section 16.

**Section: 4. FIRST AID MEASURES**

**4.1 Description of first aid measures**

**Product AS SOLD**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Get medical attention if symptoms occur.

**Product AT USE DILUTION**

- In case of eye contact : Rinse with plenty of water.
- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Get medical attention if symptoms occur.

**4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

**4.3 Indication of immediate medical attention and special treatment needed**

- Treatment : Treat symptomatically.

**Section: 5. FIREFIGHTING MEASURES**

**Product AS SOLD**

**5.1 Extinguishing media**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local

**TOPAZ LD1**

circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:  
Carbon oxides  
Sulphur oxides  
Oxides of phosphorus  
metal oxides

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

**Section: 6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

**Product AS SOLD**

Advice for non-emergency personnel : Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

**Product AT USE DILUTION**

Advice for non-emergency personnel : Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

**6.2 Environmental precautions**

**Product AS SOLD**

Environmental precautions : Do not allow contact with soil, surface or ground water.

**Product AT USE DILUTION**

Environmental precautions : No special environmental precautions required.

**6.3 Methods and materials for containment and cleaning up**

**Product AS SOLD**

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for

**TOPAZ LD1**

disposal according to local / national regulations (see section 13).  
Flush away traces with water. For large spills, dike spilled material  
or otherwise contain material to ensure runoff does not reach a  
waterway.

**Product AT USE DILUTION**

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with  
non-combustible absorbent material, (e.g. sand, earth,  
diatomaceous earth, vermiculite) and place in container for  
disposal according to local / national regulations (see section 13).  
Flush away traces with water. For large spills, dike spilled material  
or otherwise contain material to ensure runoff does not reach a  
waterway.

**6.4 Reference to other sections**

See Section 1 for emergency contact information.  
For personal protection see section 8.  
See Section 13 for additional waste treatment information.

**Section: 7. HANDLING AND STORAGE**

**7.1 Precautions for safe handling**

**Product AS SOLD**

Advice on safe handling : Avoid contact with skin and eyes. Use only with adequate  
ventilation. Wash hands thoroughly after handling. In case of  
mechanical malfunction, or if in contact with unknown dilution of  
product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety  
practice. Remove and wash contaminated clothing before re-use.  
Wash face, hands and any exposed skin thoroughly after  
handling.

**Product AT USE DILUTION**

Advice on safe handling : Wash hands after handling. In case of mechanical malfunction, or  
if in contact with unknown dilution of product, wear full Personal  
Protective Equipment (PPE). For personal protection see section  
8.

Hygiene measures : Wash hands before breaks and immediately after handling the  
product.

**7.2 Conditions for safe storage, including any incompatibilities**

**Product AS SOLD**

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store  
in suitable labeled containers.

Storage temperature : 0 °C to 40 °C

**Product AT USE DILUTION**

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store  
in suitable labeled containers.

**7.3 Specific end uses**

**TOPAZ LD1**

**Product AS SOLD**

**Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters**

**Product AS SOLD**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-(2-butoxyethoxy)ethanol	112-34-5	TWA	10 ppm 67.5 mg/m <sup>3</sup>	UKCOSSTD
		STEL	15 ppm 101.2 mg/m <sup>3</sup>	

**DNEL**

2-(2-butoxyethoxy)ethanol	:	<p>End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 101.2 mg/m<sup>3</sup></p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 20 mg/kg</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 67.5 mg/m<sup>3</sup></p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 67.5 mg/m<sup>3</sup></p>
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	:	<p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 175 mg/m<sup>3</sup></p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 2750 mg/m<sup>3</sup></p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.132 mg/m<sup>3</sup></p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 52 mg/m<sup>3</sup></p> <p>End Use: Consumers Exposure routes: Dermal</p>

**TOPAZ LD1**

	<p>Potential health effects: Long-term systemic effects Value: 1650 mg/m<sup>3</sup></p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.079 mg/m<sup>3</sup></p> <p>End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 15 mg/m<sup>3</sup></p>
--	--

**PNEC**

<p>2-(2-butoxyethoxy)ethanol</p>	<p>: Fresh water Value: 1 mg/l</p> <p>Marine water Value: 0.1 mg/l</p> <p>Intermittent use/release Value: 3.9 mg/l</p> <p>Sewage treatment plant Value: 200 mg/l</p> <p>Sediment Value: 4 mg/kg</p> <p>Soil Value: 0.4 mg/kg</p> <p>Oral Value: 56 mg/kg</p>
<p>Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt</p>	<p>: Fresh water Value: 0.24 mg/l</p> <p>Marine water Value: 0.024 mg/l</p> <p>Sewage treatment plant Value: 10000 mg/l</p> <p>Fresh water sediment Value: 0.917 mg/kg</p> <p>Marine sediment Value: 0.092 mg/kg</p> <p>Soil Value: 7.5 mg/kg</p>

**8.2 Exposure controls**

**TOPAZ LD1**

**Product AS SOLD**

**Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Individual protection measures**

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

Eye/face protection (EN 166) : Safety glasses with side-shields

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

**Product AT USE DILUTION**

**Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Individual protection measures**

Hygiene measures : Wash hands before breaks and immediately after handling the product.

Eye/face protection (EN 166) : No special protective equipment required.

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

**Environmental exposure controls**

General advice : Consider the provision of containment around storage vessels.



**TOPAZ LD1**

**Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties**

	<b>Product AS SOLD</b>	<b>Product AT USE DILUTION</b>
Appearance	: liquid	liquid
Colour	: clear, colourless	colourless
Odour	: amine-like	not significant
pH	: 8.5 - 9.5, 100 %	8.7
Flash point	: Not applicable., Does not sustain combustion.	
Odour Threshold	: Not applicable and/or not determined for the mixture	
Melting point/freezing point	: Not applicable and/or not determined for the mixture	
Initial boiling point and boiling range	: > 100 °C	
Evaporation rate	: Not applicable and/or not determined for the mixture	
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture	
Upper explosion limit	: Not applicable and/or not determined for the mixture	
Lower explosion limit	: Not applicable and/or not determined for the mixture	
Vapour pressure	: Not applicable and/or not determined for the mixture	
Relative vapour density	: Not applicable and/or not determined for the mixture	
Relative density	: 1.018 - 1.098	
Water solubility	: soluble	
Solubility in other solvents	: Not applicable and/or not determined for the mixture	
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture	
Auto-ignition temperature	: Not applicable and/or not determined for the mixture	
Thermal decomposition	: Not applicable and/or not determined for the mixture	
Viscosity, kinematic	: Not applicable and/or not determined for the mixture	
Explosive properties	: Not applicable and/or not determined for the mixture	
Oxidizing properties	: The substance or mixture is not classified as oxidizing.	

**9.2 Other information**

Not applicable and/or not determined for the mixture

**Section: 10. STABILITY AND REACTIVITY**

**Product AS SOLD**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

**TOPAZ LD1**

No dangerous reaction known under conditions of normal use.

**10.4 Conditions to avoid**

None known.

**10.5 Incompatible materials**

None known.

**10.6 Hazardous decomposition products**

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides

Sulphur oxides

Oxides of phosphorus

metal oxides

**Section: 11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Product AS SOLD**

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

**Product**

- Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg
- Acute inhalation toxicity : There is no data available for this product.
- Acute dermal toxicity : There is no data available for this product.
- Skin corrosion/irritation : There is no data available for this product.
- Serious eye damage/eye irritation : There is no data available for this product.
- Respiratory or skin sensitization : There is no data available for this product.
- Carcinogenicity : There is no data available for this product.
- Reproductive effects : There is no data available for this product.
- Germ cell mutagenicity : There is no data available for this product.
- Teratogenicity : There is no data available for this product.
- STOT - single exposure : There is no data available for this product.
- STOT - repeated exposure : There is no data available for this product.
- Aspiration toxicity : There is no data available for this product.

**Components**

**TOPAZ LD1**

Acute oral toxicity : 2-(2-butoxyethoxy)ethanol LD50 rat: 3,306 mg/kg  
Sodium p-cumenesulphonate LD50 rat: > 7,000 mg/kg  
Alkylamineoxides LD50 rat: > 1,495 mg/kg  
Amines, C12-14 alkyldimethyl, N-oxides LD50 rat: 1,064 mg/kg

**Components**

Acute dermal toxicity : 2-(2-butoxyethoxy)ethanol LD50 rabbit: 2,764 mg/kg

**Potential Health Effects**

**Product AS SOLD**

Eyes : Causes serious eye irritation.  
Skin : Health injuries are not known or expected under normal use.  
Ingestion : Health injuries are not known or expected under normal use.  
Inhalation : Health injuries are not known or expected under normal use.  
Chronic Exposure : Health injuries are not known or expected under normal use.

**Product AT USE DILUTION**

Eyes : Health injuries are not known or expected under normal use.  
Skin : Health injuries are not known or expected under normal use.  
Ingestion : Health injuries are not known or expected under normal use.  
Inhalation : Health injuries are not known or expected under normal use.  
Chronic Exposure : Health injuries are not known or expected under normal use.

**Experience with human exposure**

**Product AS SOLD**

Eye contact : Redness, Pain, Irritation  
Skin contact : No symptoms known or expected.  
Ingestion : No symptoms known or expected.  
Inhalation : No symptoms known or expected.

**Product AT USE DILUTION**

Eye contact : No symptoms known or expected.  
Skin contact : No symptoms known or expected.  
Ingestion : No symptoms known or expected.  
Inhalation : No symptoms known or expected.

**Section: 12. ECOLOGICAL INFORMATION**

**TOPAZ LD1**

**12.1 Toxicity**

**Product AS SOLD**

Environmental Effects : This product has no known ecotoxicological effects.

**Product AT USE DILUTION**

Environmental Effects : This product has no known ecotoxicological effects.

**Product AS SOLD  
Product**

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

**Components**

Toxicity to fish : 2-(2-butoxyethoxy)ethanol 96 h LC50 Fish: 1,300 mg/l

Sodium p-cumenesulphonate 96 h LC50 Oncorhynchus mykiss (rainbow trout): > 1,000 mg/l

Alkylamineoxides 96 h LC50 Danio rerio (zebra fish): 2.4 mg/l

Amines, C12-14 alkyldimethyl, N-oxides 96 h LC50: 2.67 mg/l

**Components**

Toxicity to daphnia and other aquatic invertebrates : Alkylamineoxides 48 h EC50 Daphnia magna (Water flea): 2.64 mg/l

Amines, C12-14 alkyldimethyl, N-oxides 48 h EC50 Daphnia magna (Water flea): 3.1 mg/l

**Components**

Toxicity to algae : Sodium p-cumenesulphonate 96 h EC50 Pseudokirchneriella subcapitata (algae): > 230 mg/l

Alkylamineoxides 72 h EC50 Pseudokirchneriella subcapitata (green algae): 0.266 mg/l  
28 d NOEC: > 0.067 mg/l

Amines, C12-14 alkyldimethyl, N-oxides 72 h LC50: 0.143 mg/l  
72 h NOEC: 0.067 mg/l

**12.2 Persistence and degradability**

**Product**

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

**Components**

Biodegradability : 2-(2-butoxyethoxy)ethanol Result: Readily biodegradable.

Sodium p-cumenesulphonate Result: Readily biodegradable.

**TOPAZ LD1**

Fattyalcohol ethoxylates  $\leq$  C15 and  $\leq$  5EO Result: Readily biodegradable.

Alkylamineoxides Result: Readily biodegradable.

Amines, C12-14 alkyldimethyl, N-oxides Result: Readily biodegradable.

**12.3 Bioaccumulative potential**

no data available

**12.4 Mobility in soil**

no data available

**12.5 Results of PBT and vPvB assessment**

**Product**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects**

no data available

**Section: 13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

**13.1 Waste treatment methods**

**Product AS SOLD**

Product : Do not contaminate storm water drains, natural waterways or soil with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

**TOPAZ LD1**

**Product AT USE DILUTION**

- Product : Diluted product can be flushed to sanitary sewer if regulations permit.
- Contaminated packaging : Dispose of in accordance with local, state, and federal regulations.

**Section: 14. TRANSPORT INFORMATION**

**Product AS SOLD**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

**Land transport (ADR/ADN/RID)**

- 14.1 UN number : Not dangerous goods
- 14.2 UN proper shipping name : Not dangerous goods
- 14.3 Transport hazard class(es) : Not dangerous goods
- 14.4 Packing group : Not dangerous goods
- 14.5 Environmental hazards : Not dangerous goods
- 14.6 Special precautions for user : Not dangerous goods

**Air transport (IATA)**

- 14.1 UN number : Not dangerous goods
- 14.2 UN proper shipping name : Not dangerous goods
- 14.3 Transport hazard class(es) : Not dangerous goods
- 14.4 Packing group : Not dangerous goods
- 14.5 Environmental hazards : Not dangerous goods
- 14.6 Special precautions for user : Not dangerous goods

**Sea transport (IMDG/IMO)**

- 14.1 UN number : Not dangerous goods
- 14.2 UN proper shipping name : Not dangerous goods
- 14.3 Transport hazard class(es) : Not dangerous goods
- 14.4 Packing group : Not dangerous goods
- 14.5 Environmental hazards : Not dangerous goods
- 14.6 Special precautions for user : Not dangerous goods
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not dangerous goods

**Section: 15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**TOPAZ LD1**

according to Detergents : 5 % or over but less than 15 %: Phosphates  
 Regulation EC 648/2004 less than 5 %: Anionic surfactants, Non-ionic surfactants,  
 Polycarboxylates  
 Preservation agents:  
 2-phenoxyethanol

Seveso III: Directive : Not applicable.  
 2012/18/EU of the European  
 Parliament and of the Council  
 on the control of major-  
 accident hazards involving  
 dangerous substances.

Candidate List of Substances : Not applicable.  
 of Very High Concern for  
 Authorisation

**National Regulations**

**Take note of Dir 94/33/EC on the protection of young people at work.**

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)  
 Regulations.  
 The Control of Substances Hazardous to Health Regulations.  
 Health and Safety at Work Act.

**15.2 Chemical Safety Assessment**

No Chemical Safety Assessment has been carried out on the product.

**Section: 16. OTHER INFORMATION**

**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Eye irritation 2, H319	Calculation method

**Full text of H-Statements**

H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H400 Very toxic to aquatic life.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.

**Full text of other abbreviations**

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and

**TOPAZ LD1**

Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Annex: Exposure Scenarios**

**Exposure Scenario: Foam cleaner. Semi-Automatic without venting process**

Life Cycle Stage : Use at industrial sites  
Product category : **PC35** Washing and cleaning products (including solvent based products)

**Contributing scenario controlling environmental exposure for:**

Environmental release category : **ERC4** Industrial use of processing aids in processes and products, not becoming part of articles  
Daily amount per site : 50 kg  
Type of Sewage Treatment Plant : Municipal sewage treatment plant



**TOPAZ LD1**

**Contributing scenario controlling worker exposure for:**

Process category : **PROC7** Industrial spraying  
Exposure duration : 240 min  
Operational conditions and risk management measures : Indoor  
Local Exhaust Ventilation is not required  
General ventilation Ventilation rate per hour 1  
Skin Protection : see section 8  
Respiratory Protection : see section 8

**Contributing scenario controlling worker exposure for:**

Process category : **PROC8b** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities  
Exposure duration : 60 min  
Operational conditions and risk management measures : Indoor  
Local Exhaust Ventilation is not required  
General ventilation Ventilation rate per hour 1  
Skin Protection : see section 8  
Respiratory Protection : see section 8

**Exposure Scenario: Foam cleaner. Semi-Automatic with venting process**

Life Cycle Stage : Use at industrial sites  
Product category : **PC35** Washing and cleaning products (including solvent based products)

**Contributing scenario controlling environmental exposure for:**

Environmental release category : **ERC4** Industrial use of processing aids in processes and products, not becoming part of articles  
Daily amount per site : 50 kg  
Type of Sewage Treatment Plant : Municipal sewage treatment plant

**Contributing scenario controlling worker exposure for:**

Process category : **PROC7** Industrial spraying  
Exposure duration : 240 min

**TOPAZ LD1**

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

**Contributing scenario controlling worker exposure for:**

Process category : **PROC8b** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

**Exposure Scenario: General purpose cleaner. Manual process**

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

**Contributing scenario controlling environmental exposure for:**

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

**Contributing scenario controlling worker exposure for:**

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

**TOPAZ LD1**

General ventilation	Ventilation rate per hour	1
Skin Protection	: see section 8	
Respiratory Protection	: see section 8	

**Contributing scenario controlling worker exposure for:**

Process category	: <b>PROC8a</b>	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
Exposure duration	: 60 min	
Operational conditions and risk management measures	: Indoor	
		Local Exhaust Ventilation is not required
General ventilation	Ventilation rate per hour	1
Skin Protection	: see section 8	
Respiratory Protection	: see section 8	