DISTILAMAX® GW

Yeast developed for use in the production of grain Whisky and Whiskey

Technical Data Sheet


APPLICATIONS:

- DistilaMax GW is recommended for use in the production of whisky and whiskey by fermentation of wort made from wheat or corn. It is also suitable for the production of American style whiskies from various whole grain fermentations.
- DistilaMax GW has a short lag phase and ensures a very quick start of fermentation which reduces the risks of contamination by wild yeast and bacteria.
- DistilaMax GW displays good temperature tolerance and performs well from 20°C up to 34°C.
- DistilaMax GW produces a clean congener profile that is well-suited to grain whisky and whiskey.

RESULTS WITH DISTILAMAX GW:

DistilaMax GW, when compared with two other yeasts specifically selected for corn-based mash, performs well in regards to the kinetics of fermentation along with the production of congeners which are favourable to whiskies, as demonstrated in figures 1 and 2.

Results of Ethanol content (%v/v) comparison with 3 yeast strains in 100% corn mash



Results of congener comparison of 3 yeast strains in 100% corn mash




Figure 1: Trial LBDS 2018.

Figure 2: Trial LBDS 2018.

Isoamyl acetate: Banana-like aroma Ethyl decanoate: Floral-like aromas Ethyl octanoate: Floral-like aromas



DISTILAMAX® GW

Yeast developed for use in the production of grain Whisky and Whiskey

Technical Data Sheet

CHARACTERISTICS:

Solids (Dry Weight): 95.5 +/-2.5%
 Viable Cells (CFU/g): >1x10e10
 Total Wild Yeast (CFU/g): <1000

DistilaMax GW is not genetically modified and is Kosher.

DOSAGE:

- The optimal yeast dosage is variable according to individual distillery production processes.
- Fermentation of malted barley for whisky production: 0.50 1.0 grams per litre of wort (dosage: 500 1000 ppm).
- Fermentation of on grain mashes for whiskey production: 0.25 0.50 grams per litre of mash (dosage: 250 500 ppm).

INSTRUCTIONS OF USE:

Lallemand Biofuels & Distilled Spirits recommends the rehydration of DistilaMax GW.

- 1. For rehydration, use a clean container. Do not use demineralized water.
- 2. Rehydrate the yeast in clean water (the water should be 10 times the weight of the yeast and at a temperature of 36°C 38°C).
- Suspend contents carefully by gently stirring and then wait for 15 20 minutes maximum (minimum 10 minutes) before moving onto the next step.
- 4. Add this preparation to the wash. If there is a temperature difference of more than 8°C between the wash to be inoculated and the rehydration solution, add some wash slowly into the rehydration solution to reduce the temperature difference.
- 5. Once the vacuum-sealed bag is open or broken, use yeast promptly.

0.50 - 1.0g/L Potable Water 36°C - 38°C

STORAGE, HANDLING & PACKAGING:

- DistilaMax GW should be stored in a cool and dry area away from heat and direct sunlight for maximum stability.
- Shelf Life: 3 years from date of manufacture if vacuum-seal is not broken.
- Packaging: DistilaMax GW is available in vacuum-sealed foil bags in 10 kilograms or boxes of 20 x 500 grams.

To the best of our knowledge, the information contained here is true and accurate.

However, any recommendations or suggestions are made without any warranty or guarantee since conditions and methods of use are beyond our control. This information should not be considered as a recommendation that our products be used in violation of any patents.





