

PPWR Intermediate Declaration of Conformity

1. Unique identification of the declaration

Document number: 1.4.1.3
Version: 1
Issue date: 23/07/2026

2. Manufacturer

Company name: DISPACK-Projects NV
Address: Admiraalhof 24
Postal code & City: 9070 Destelbergen
Country: Belgium
Authorised representative: Marnix Kuypers

3. Statement of responsibility

We hereby declare that this PPWR Declaration of Conformity is issued under our sole responsibility.

4. Subject of the declaration

Packaging type: Dolium One-Way Keg

Packaging name: Dolium 30 L Prime types A, G, S, D
Dolium 24 L Prime types A, G, S, D
Dolium 20 L Slim Line types A, G, S, D
Dolium 12,5 L Slim Line types A, G, S, D

5. Description of the packaging

Intended use:

- The Dolium One-Way Kegs are intended to be used for all aqueous and acidic foods and alcoholic foods up to an alcohol content of 20%;
- Filling temperature between 0°C and 35°C;
- Suitable for long-term storage at room temperature or below.



Materials and composition:

Dolium 30 L Prime types A, G, S, D

DOLIUM 30L-A/G/S/D SLIM LINE - CO2				TYPE A		TYPE G		TYPE S		TYPE D	
PARTS	MATERIAL	COLOR	FOOD contact	WEIGHT		WEIGHT		WEIGHT		WEIGHT	
				gr	%	gr	%	gr	%	gr	%
Body	PET	natural	Y	446,7	36,6%	446,7	36,8%	446,7	36,3%	446,7	36,3%
	PA-MXD6	natural	Y	22,8	1,9%	22,8	1,9%	22,8	1,8%	22,8	1,8%
	PET-colorant	amber	Y	9,6	0,8%	9,6	0,8%	9,6	0,8%	9,6	0,8%
Top ring	HDPE	black	N	332,6	27,2%	332,6	27,4%	332,6	27,0%	332,6	27,0%
Bottom ring	HDPE	black	N	273,0	22,4%	273,0	22,5%	273,0	22,2%	273,0	22,2%
Glue	PU-based	black	N	12,0	1,0%	12,0	1,0%	12,0	1,0%	12,0	1,0%
Body Upper	PA6 - GF30	black	Y	38,1	3,1%	31,8	2,6%	29,5	2,4%	29,5	2,4%
Body Lower	PA6 - GF30	black	Y	11,8	1,0%	11,8	1,0%	22,7	1,8%	22,7	1,8%
Beer valve / stem	PA6 - GF30	black	Y	7,3	0,6%	7,3	0,6%	4,2	0,3%	5,4	0,4%
Clips 2x	PA6 - GF30	black	N	21,6	1,8%	21,6	1,8%	21,6	1,8%	21,6	1,8%
Spear parts	PP-GF30	red	Y	3,8	0,3%	3,8	0,3%	10,6	0,9%	7,8	0,6%
Tube	LDPE	natural	Y	14,8	1,2%	14,8	1,2%	13,4	1,1%	13,4	1,1%
Springs	Stainless	natural	Y	21,8	1,8%	21,8	1,8%	26,1	2,1%	26,1	2,1%
Spear seal part	SBC/TPE-S	natural	Y	3,5	0,3%	3,5	0,3%	5,6	0,5%	5,8	0,5%
O-rings	EPDM	black	Y	1,2	0,1%	1,2	0,1%	1,6	0,1%	1,6	0,1%
Keg label	PET - PA6	white	N	0,2	0,0%	0,2	0,0%	0,2	0,0%	0,2	0,0%
Glue	UV-acrylic	natural	N	0,03	0,0%	0,03	0,0%	0,03	0,0%	0,03	0,0%
TOTAL (P=0bar)				1.220,76	100,0%	1.214,46	100,0%	1.232,15	100,0%	1.230,77	100,0%

Dolium 24 L Prime types A, G, S, D

DOLIUM 24L-A/G/S/D SLIM LINE - CO2				TYPE A		TYPE G		TYPE S		TYPE D	
PARTS	MATERIAL	COLOR	FOOD contact	WEIGHT		WEIGHT		WEIGHT		WEIGHT	
				gr	%	gr	%	gr	%	gr	%
Body	PET	natural	Y	446,7	36,7%	446,7	36,9%	446,7	36,3%	446,7	36,4%
	PA-MXD6	natural	Y	22,8	1,9%	22,8	1,9%	22,8	1,8%	22,8	1,9%
	PET-colorant	amber	Y	9,6	0,8%	9,6	0,8%	9,6	0,8%	9,6	0,8%
Top ring	HDPE	black	N	332,6	27,3%	332,6	27,4%	332,6	27,0%	332,6	27,1%
Bottom ring	HDPE	black	N	273,0	22,4%	273,0	22,5%	273,0	22,2%	273,0	22,2%
Glue	PU-based	black	N	12,0	1,0%	12,0	1,0%	12,0	1,0%	12,0	1,0%
Body Upper	PA6 - GF30	black	Y	38,1	3,1%	31,8	2,6%	29,5	2,4%	29,5	2,4%
Body Lower	PA6 - GF30	black	Y	11,8	1,0%	11,8	1,0%	22,7	1,8%	22,7	1,8%
Beer valve / stem	PA6 - GF30	black	Y	7,3	0,6%	7,3	0,6%	4,2	0,3%	5,4	0,4%
Clips 2x	PA6 - GF30	black	N	21,6	1,8%	21,6	1,8%	21,6	1,8%	21,6	1,8%
Spear parts	PP-GF30	red	Y	3,8	0,3%	3,8	0,3%	10,6	0,9%	7,8	0,6%
Tube	LDPE	natural	Y	12,5	1,0%	12,5	1,0%	11,1	0,9%	11,1	0,9%
Springs	Stainless	natural	Y	21,8	1,8%	21,8	1,8%	26,1	2,1%	26,1	2,1%
Spear seal part	SBC/TPE-S	natural	Y	3,5	0,3%	3,5	0,3%	5,6	0,5%	5,8	0,5%
O-rings	EPDM	black	Y	1,2	0,1%	1,2	0,1%	1,6	0,1%	1,6	0,1%
Keg label	PET - PA6	white	N	0,2	0,0%	0,2	0,0%	0,2	0,0%	0,2	0,0%
Glue	UV-acrylic	natural	N	0,03	0,0%	0,03	0,0%	0,03	0,0%	0,03	0,0%
TOTAL (P=0bar)				1.218,48	100,0%	1.212,18	100,0%	1.229,88	100,0%	1.228,48	100,0%



Dolium 20 L Slim Line types A, G, S, D

DOLIUM 20L-A/G/S/D SLIM LINE - CO2				TYPE A		TYPE G		TYPE S		TYPE D	
PARTS	MATERIAL	COLOR	FOOD contact	WEIGHT		WEIGHT		WEIGHT		WEIGHT	
				gr	%	gr	%	gr	%	gr	%
Body	PET	natural	Y	361,7	37,6%	361,7	37,8%	361,7	37,1%	361,7	37,2%
	PA-MXD6	natural	Y	18,4	1,9%	18,4	1,9%	18,4	1,9%	18,4	1,9%
	PET-colorant	amber	Y	7,4	0,8%	7,4	0,8%	7,4	0,8%	7,4	0,8%
Top ring	HDPE	black	N	246,6	25,6%	246,6	25,8%	246,6	25,3%	246,6	25,4%
Bottom ring	HDPE	black	N	192,2	20,0%	192,2	20,1%	192,2	19,7%	192,2	19,8%
Glue	PU-based	black	N	12,0	1,2%	12,0	1,3%	12,0	1,2%	12,0	1,2%
Body Upper	PA6 - GF30	black	Y	38,1	4,0%	31,8	3,3%	29,5	3,0%	29,5	3,0%
Body Lower	PA6 - GF30	black	Y	11,8	1,2%	11,8	1,2%	22,7	2,3%	22,7	2,3%
Beer valve / stem	PA6 - GF30	black	Y	7,3	0,8%	7,3	0,8%	4,2	0,4%	5,4	0,6%
Clips 2x	PA6 - GF30	black	N	21,6	2,2%	21,6	2,3%	21,6	2,2%	21,6	2,2%
Spear parts	PP-GF30	red	Y	3,8	0,4%	3,8	0,4%	10,6	1,1%	7,8	0,8%
Tube	LDPE	natural	Y	14,8	1,5%	14,8	1,5%	13,4	1,4%	13,4	1,4%
Springs	Stainless	natural	Y	21,8	2,3%	21,8	2,3%	26,1	2,7%	26,1	2,7%
Spear seal part	SBC/TPE-S	natural	Y	3,5	0,4%	3,5	0,4%	5,6	0,6%	5,8	0,6%
O-rings	EPDM	black	Y	1,2	0,1%	1,2	0,1%	1,6	0,2%	1,6	0,2%
Keg label	PET - PA6	white	N	0,2	0,0%	0,2	0,0%	0,2	0,0%	0,2	0,0%
Glue	UV-acrylic	natural	N	0,03	0,0%	0,03	0,0%	0,03	0,0%	0,03	0,0%
TOTAL (P=0bar)				962,43	100,0%	956,13	100,0%	973,82	100,0%	972,42	100,0%

Dolium 12,5 L Slim Line types A, G, S, D

DOLIUM 12,5L-A/G/S/D SLIM LINE - CO2				TYPE A		TYPE G		TYPE S		TYPE D	
PARTS	MATERIAL	COLOR	FOOD contact	WEIGHT		WEIGHT		WEIGHT		WEIGHT	
				gr	%	gr	%	gr	%	gr	%
Body	PET	natural	Y	361,7	37,7%	361,7	38,0%	361,7	37,3%	361,7	37,4%
	PA-MXD6	natural	Y	18,4	1,9%	18,4	1,9%	18,4	1,9%	18,4	1,9%
	PET-colorant	amber	Y	7,4	0,8%	7,4	0,8%	7,4	0,8%	7,4	0,8%
Top ring	HDPE	black	N	246,6	25,7%	246,6	25,9%	246,6	25,4%	246,6	25,5%
Bottom ring	HDPE	black	N	192,2	20,1%	192,2	20,2%	192,2	19,8%	192,2	19,9%
Glue	PU-based	black	N	12,0	1,3%	12,0	1,3%	12,0	1,2%	12,0	1,2%
Body Upper	PA6 - GF30	black	Y	38,1	4,0%	31,8	3,3%	29,5	3,0%	29,5	3,0%
Body Lower	PA6 - GF30	black	Y	11,8	1,2%	11,8	1,2%	22,7	2,3%	22,7	2,3%
Beer valve / stem	PA6 - GF30	black	Y	7,3	0,8%	7,3	0,8%	4,2	0,4%	5,4	0,6%
Clips 2x	PA6 - GF30	black	N	21,6	2,3%	21,6	2,3%	21,6	2,2%	21,6	2,2%
Spear parts	PP-GF30	red	Y	3,8	0,4%	3,8	0,4%	10,6	1,1%	7,8	0,8%
Tube	LDPE	natural	Y	10,5	1,1%	10,5	1,1%	9,1	0,9%	9,1	0,9%
Springs	Stainless	natural	Y	21,8	2,3%	21,8	2,3%	26,1	2,7%	26,1	2,7%
Spear seal part	SBC/TPE-S	natural	Y	3,5	0,4%	3,5	0,4%	5,6	0,6%	5,8	0,6%
O-rings	EPDM	black	Y	1,2	0,1%	1,2	0,1%	1,6	0,2%	1,6	0,2%
Keg label	PET - PA6	white	N	0,2	0,0%	0,2	0,0%	0,2	0,0%	0,2	0,0%
Glue	UV-acrylic	natural	N	0,03	0,0%	0,03	0,0%	0,03	0,0%	0,03	0,0%
TOTAL (P=0bar)				958,16	100,0%	951,86	100,0%	969,56	100,0%	968,16	100,0%

6. Conformity statement

We hereby declare that the packaging described above complies with Regulation (EU) 2025/40 (PPWR), including Articles 5 to 12.

With regards to the PFAS content < 50ppm, we inform you that today we meet between 98.9% and 99.7% (dependant of keg and spear type) of the total keg balance. We are still waiting for the laboratory test results from 1 of our suppliers to cover the remaining 4 - 10 gr of spear parts.

A new Declaration of Conformity will be issued as soon as PFAS is 100% conform.

7. Reference to technical documentation

Technical file document number:

1.4.1.4	PPWR_Dolium 30 L Prime TD
1.4.1.5	PPWR_Dolium 24 L Prime TD
1.4.1.6	PPWR_Dolium 20 L Slime line TD
1.4.1.7	PPWR_Dolium 12.5 L Slim line TD

8. Signature

Place: Antwerp

Date: 23/07/2026

Name: Marnix Kuypers

Function: C.E.O.

Signature:



Note:

This statement has been prepared based on the current status of the PPWR regulations and may be amended should future legislative changes require it.